

### ALSTASAN SILVOX 150

Silver Hydrogen Peroxide based Spray Disinfectant

#### Product Composition:

Hydrogen Peroxide IP: 11.0% w/w

Silver Nitrate: 150 ppm

Inert matter (Solvent and Stabilizers): Balance

#### Application

*Human Disinfection System*

#### Directions for Use

##### Sanitation by Spraying Method

Dilution Ratio – 1% Dilution

Coverage – Sprayed and allowed a minimum contact time of 5 seconds, wipe off if necessary.

*Kindly refer to your nearest CSL representative for exact dosage and application method.*

#### Material Compatibility

- **Compatibles:** Rubber Hose, Plastic Nozzles, Piping System and Stainless Steel.
- **Incompatibles:** Mild Steel, Cast Iron, Copper and Aluminum



#### Handling Measures and Precautions

Proper safety products such as splash goggles, gloves should be worn while handling and applying chemicals. Splashes on skin to be washed off with water immediately. In case of splashing into the eyes, flush them with fresh water and seek medical attention. Should not be injected. *Kindly refer to SDS for more details.*

#### Packing

ALSTASAN SILVOX 150 is available in 20L HDPE jars.

#### Chemtex Speciality Ltd.

Haute Street Corporate Park, 86A Topsia Road (S), Kolkata – 700046, India

Telephone : +91-33-7111-1111 | Fax: +91-33-7111-1117

Email: [info@chemtexlimited.com](mailto:info@chemtexlimited.com) | URL: [www.chemtexltd.com](http://www.chemtexltd.com)

**ISO 9001, ISO 14001, OHSAS 18001, CRISIL, GMP, MSME certified**

Disclaimer: The content of this information sheet is for the website of Chemtex Speciality Ltd and may be legally privileged for copyright ©. The information stated herein is for web promotion and should not be treated as original product specification. Please refer to original specification Sheet before placing order to confirm its end use application and true specification. Other third party tradenames may be used for the reference of readers only and the company does not intend or claim to offer or sell them.

